



Yiwu Xinyuan Technology Co.,Ltd.


Tel:+86 188 6816 8090 (Kris)

Email:kris@xypedestal.com


Web:www.xypedestal.com

Add:Intelligence Pioneer Park,Fotang Town,Yiwu,China

Adjustable Pedestal XY-M4-PA Data Sheet




Composition




1 head(80mm)+ 1 spacer+1 shim +5 fix collar+4 extender +1

Details

Spacer tabs
thickness:
2mm/5mm
/6mm/10mm



Shim: anti-slip,
reduce impact,
absorb shock
and sound,
compensate floor
thickness
difference.




Height Range

425mm-690mm

Material

Composition:90%PP,10% talc,UV adn black masterbatch;
100% recyclable

Slope corrector:
compensate
slope 0%-5%



Performances

Resisting UV rays,weather, sea salt and almost all chemicals
Temperature range :-40℃ to 120℃

Application area

Support for outdoor terraces with any kind of material:timber decking,
stone,ceramic,composite materials,metal,fiberglass grid.
Can be placed on any stable substrate,aslo over insulation panels.

Fix collar:
fix and lock
height after
adjustment,
increase stability
of pedestal



Red collar,
customized collar
accept.
Made of PP

Slope corrector

Slope correctors could compensate ground fall 0%-5%
making ideal levelling surface.
choose to use it or not with different installing conditions.

Compression test

Performed on the full(1/1),half(1/2)and quarter(1/4) surface of the head

Position	Height(mm)	Breaking Load(kgs)
1/1	600	1594
1/2	600	1354
1/4	600	810

Weight(g/set)

spacer	17	head	230
shim	30	base	295
fix collar	29	extender	320
Total		2000	

Safety value for maximum allowable load by compression for XY-M4-PA:
★Safety for pedestrian terraces:divide the load indicated in the table by 2
with a safety factor of -15%
★Safety for technical floor:divide the load indicated in the table by 4 with
a safety factor of -15%